# Wireflow free-form



## 0351


Design By Arik Levy

Wireflow designed by Arik Levy. Hanging lap. The elegant structure of fine cables and LED terminal by Wireflow allows the combination of multiple individual pieces to carry out major graphic lighting installations which generate a visual opportunity of lines and points of light and bring a markedly conceptual character to an intangible product. The electrical connection point can be positioned on the ceiling or wall.

## Model Sheet







Optional: Extra cable length
Min. quantity, upcharge and extra lead time
apply [EN]

Finish 04 Black
RAL 9005

LED temperature 2700 K / 3000 K / 3500 K / 4000 K

Dimming DALI 1-10V Push / CASAMBI

Surface Canopy

Materials Ceiling rose: Steel
Body: Aluminum
Rods: Steel

Instalation type

Light source  $4 \times LED 4,48W 350mA$ 

LED CRI>90 1961 lm 109

2700 K / 3000 K / 3500 K / 4000 K

**Driver** Constant Current 350 110~240 V V 50~60 Hz HZ

Dimmable LED

IP20 Bi-volt 50-60Hz

Application

Packaging 1Box

0.42 m x 0.42 m x 0.25 m Gross weigth 6 Net weigth 5 Vol. 0.0441

Hanging lamps

#### Lighting effect

#### **General Lighting**

Lamp for general lighting that equally distributes the light in all directions.



### Photometric Data

Efficiency 40.11%
Coordinate System CG
Total Flux 1961.10
Maximum Value 54.19

All of our products come with a five-year warranty. Check our legal terms at www.vibia.com/warranty