

GUISE

Design by Stefan Diez.

VIBIA

Reference

2272.

Application

Hanging lamps

Installation type

Surface

Description

Vibia presents a pendant lamp where the light source is invisible, emanating directly from the material. The light is equipped with a counterweight placed on the ground with a cable with plug for this reason it is not necessary to have a light point on the ceiling.

Diffuser

Difusor de vidrio borosilicato transparente

Materials

Profile: Aluminum

Diffuser: Borosilicate glass

Finish



2272-18 Matt graphite lacquer (ADAPTA RF 9913 WX)

Sketch



Electrical characteristics



Led 3000K CRI >90 1742 lm 87 lm/W

Fixture: 905.64 lm 35.8 lm/W

Driver included: CC - Constant Current 100-240V 50/60Hz

Electronic dimming OPTICAL SENSOR

Physical characteristics

1 Box / 0.00 x 0.00 x 0.00 m. / Vol. 0.1470 m³ /

Gross weight 7.0 kg. / Net weight 5.0 kg.


Installation and assembly

Please, see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 905.64 lm

Maximum value : 195.12 cd/klm

Light position : C=15.00 G=35.00

Symmetry on the planes : Double symmetrical

Isolux : Isolux (Floor)

Light position :

X=0.00ft Y=0.00ft Z=8.20ft

Certificates

